20m WFSV

Crew Transfer Vessel



General characteristics

StructureAluminiumS/Structure MountingWeldedClassificationOptional

Flag UK, MCA Workboat Code, Category | MGN280(M)

Dimensions

 Length O.A.
 20.30 m

 Beam O.A.
 6.40 m


 Depth
 2.40 m


Draft (max) 1.55 m (including Skeg)

Displacement (lightship) 41 tonnes



20m WFSV Crew Transfer Vessel





Capacities

Fuel oil 8,500 L Fresh water 1,000 L Black water 500 L Free workdeck area 40 m^2 1.5 t/m² Max deck load Deck cargo 5 tonne Crew <3 persons <12 persons **Passengers**

Performance

 Speed (max)
 28.0 knots (460 litres/hr)

 Speed (high)
 26.0 knots (410 litres/hr)

 Speed (low)
 24.0 knots (360 litres/hr)

Propulsion system

Speed (max) 2 x Caterpillar C32 'C Rating'
Total power 2 x 970 kW (2 x 1319 hp)
Gearbox 2 x Twin Disc MGX6620A
Propulsion Fixed Pitch Propulsion

Electrical equipment

Network 24V DC, 230V 50 Hz AC Generator set 2×17.5 kW, 1×6.5 kW

Deck layout

Anchor equipment I x 40 kg Bruce with chain and line,

AAW-110 Winch

Bow fendering RG Seasight T Fender Secondary access Osbit MaXccess / TDD

(Tube Docking Device) / VGRIP

Deck crane Palfinger PK6500 (optional)

Mob recovery system Ship Mounted Davit and fibrelight cradle

Life saving equipment

Life buoys 3 Life jackets 17

Life rafts 2×16 persons

Fire fighting Stat-X Fi-Fi system in engine rooms

Portable hand operated Fi-Fi in other areas

Accommodation

Accommodation $12 \times Saloon Seats, 2 \times Crew Cabins,$

Galley/Mess Area, I x Heads,

2 x Bridge Seats

Noise levels <70dBa

All published information is for guidance only, is not guaranteed and is subject to change. Vessel branding is based nominally on hull length and is indicative only.

